



Italian excellence since 1906

PAN92341 1/3 HP Sump Pump

- Energy efficient 1/3 HP split capacitor motor. Lower amp draw, runs cooler, lasts longer.
- Rugged solid cast iron pump base & cast iron pump housing.
- Hermetically sealed, oil cooled motor for long pump life.
- Automatic vertical float switch.
- Stainless steel impeller
- 1-1/2" NPT discharge
- Handles up to 3/8" solids.
- Motor is thermally protected with automatic reset thermal protector.
- Stainless steel motor shaft
- Carbon/ceramic/stainless steel mechanical shaft seal.
- Upper and lower permanently lubricated ball bearings.
- Stainless steel fasteners
- Bottom screen removes easily for cleaning.
- Acceptable for indoor or outdoor use.
- Compact, lightweight design is easily portable.
- Every unit is 100% pressure tested.



2760 GPH

5 Year Warranty


PAN92341 1/3HP Sump Pump

| Motor Specifications | |
|----------------------|---------------------------------------|
| Horsepower | 1/3 HP |
| Voltage | 120 |
| Amps | 4.1 |
| Hertz | 60 Hz |
| Phase | Single |
| RPM | 3450 RPM |
| Motor Type | Permanent Split Capacitor (PSC) |
| Insulation | Class A |
| Circuit Requirements | 15 amp (min) individual circuit |
| Duty Rating | Continuous* |
| Shaft Seal | Carbon/ceramic and stainless steel |
| Motor Shaft | Stainless Steel |
| Upper Motor Bearing | Ball Bearing |
| Lower Motor Bearing | Ball Bearing |
| Cooling | Oil cooled |
| Motor Protection | Auto reset thermal overload protector |

*For continuous operation, the water depth must be at least 6" to prevent the motor from overheating.

| Pump Specifications | |
|---------------------|-----------------------------------|
| Discharge Size | 1-1/2" NPT |
| Cord Length | 10' |
| Cord Type | SJTW, UL listed, 3-wire, 18 gauge |
| Pump Housing | Cast iron |
| Pump Base | Cast iron |
| Impeller Material | Stainless steel |
| Impeller Type | Stainless steel |
| Gasket | Buna-N |
| Solids Handling | 3/8" spherical |
| Liquid Temp. Range | 32°- 120° F |
| Operation | Automatic or non-automatic |
| Fasteners | Stainless steel |
| Max Flow Rate | 46 Gallons per minute |
| Maximum Head | 25 feet |
| Max Pressure | 10.8 psi |
| Weight | 17.0 lbs |

| Automatic Switch Specifications | |
|---------------------------------|-----------------------------------|
| Type | SJE Rhombus Vertical Master II |
| Switch on point | 10' |
| Switch off point | 2" |
| Material | High impact PVC |
| Cord Type | SJOW, UL listed, 2-wire, 18 gauge |



PERFORMANCE CHART

| Head | 0 ft. | 5 ft. | 10 ft. | 15 ft. | 20 ft. | 25 ft. |
|------|-------|-------|--------|--------|--------|--------|
| GPM | 46 | 36 | 30 | 25 | 12 | 1 |
| GPH | 2780 | 2160 | 1800 | 1500 | 720 | 60 |

Dimensions

